TOC DDACC AND DDON'S	7F WORKS II		Model N	No.
T&S BRASS AND BRONZE WORKS, INC. 2 SADDLEBACK COVE / P.O. BOX 1088 / TRAVELERS REST, SC 29690			0119	15-40
2 SADDLEDACK COVE / P.O. BOX 1000 / PHONE 800-476-4103	FAX 864- 834-	7540	Item No	D.:
	Architect/Engineer	ISO "#900)2	
Job Nullie.	Architect/ Engineer	Approvai.		
Notes:				
	1/4" DIA. MOUNTIN	G HOLES		
	1/2" NPT FEMALE			
5 1/4" 4 1/0" 2 7/16"				7 3 3/4" 95mm]
5 1/4" 4 1/2" 2 7/16" [133mm] [114mm] [62mm] 1 7/32" [31mm]		$\overline{}$		95mm]
	1/2" NPT FEMAL			
<u> </u>	7			
4"	1/2" NPT FE	CMALE HOT INLE	ST .	↑ 20 7/16
[25mm] -	///			[520mm]MAX.
→	15/16"			RAISED FOR CLEANING
	[49mm] \\\\		<i>^</i>	_
		/	', <u> </u>	
NOTE 1: ALL PEDAL POSITION		<i>}!</i>	/	
DIMENSIONS ARE BASED ON MINIMUM RECOMMENDED MOUNTING HEIGHT OF WALL	<i>[]</i>	,///		
8 3/4" [222mm] ABOVE FIN. FLOOR	//			
2 5/16 — 2 5/8" — [67mm]	⊢ ///		40.5	- /40
[59mm]			16 5 [414mi	m]WHEN
V V IN OUT IN OUT			RAISEI CLEA	D FOR
→ +				
1 15/16"	Y			
[49mm] T		PEDAL HEIG	HT	
8 3/4" MIN.	ADI FROM 2	— ADJUSTING : 1/8"[54mm]-6		
[222mm] (SEE NOTE 1)	WHEN VAI	LVE CLOSED, 1/	′4"[6mm]–	
2 1/4"	2 5/8"[6"	7mm] WHEN VA	TAME ODEN —	
[57mm]				
FLOOR —	\neg			
	 			
	ADJ. FROM 14 1/		1	
15 3/8"[390mm] WHEN CLOSED, 13 1/2"[343mm] TO 14 3/4"[375mm]				
NOTE 2. FURNISHED WITH (2) WOOD MOUNTING SCREWS	WHEN ()PEN	····]	
Product Description:		rawn:	Checked	Scale:
	V	VJS	JRM	1:4
B-0504 DOUBLE PEDAL VALVE FO	R DELTA	pproved		Date:
		IНВ		02/03/06