## T&S BRASS AND BRONZE WORKS, INC. PHONE 800-476-4103

STRAIGHT LOOSE KEY STOP



Model No.
B-0508-LKS
Item No.:

2 SADDLEBACK COVE / P.O. BOX 1088 / TRAVELERS REST, SC 29690 FAX 864-834-3518 Job Name: Architect/Engineer Approval: Notes: 2 5/8" [67mm] 1/4" DIA. MOUNTING HOLES 1/2" NPT FEMALE INLET 3 5/8" 2 3/4" 1 3/4" [25mm] [92mm] [70mm] [44mm] 1 3/8" [35mm] -1/2" NPT FEMALE OUTLET 1" [25mm]-1 15/16" [49mm] -WALL -20 7/16" 1 7/8" [519mm] MAX. [48mm] RAISED FOR CLEANING 1 1/8" [29mm] 1 15/16" 19 3/4"[501mm] WHEN [49mm] RAISED FOR CLEANING LOOSE KEY STRAIGHT STOP IN OUT ⁄2 1<sup>T</sup>/2" [63ṃm] PEDAL HEIGHT ADJUSTING SCREW 8 3/4" MIN. [222mm] ADJ. FROM 2 1/8"[54mm]-6 1/4"[159mm] (SEE NOTE 1) WHEN VALVE CLOSED, 1/4"[6mm]-2 1/4" 2 5/8"[67mm] WHEN VALVE OPEN [57mm] **FLOOR** ADJ. FROM 14 1/2"[368mm] T0 15 3/8"[390mm] WHEN CLOSED,13 1/2"[343mm] NOTE 1. ALL PEDAL POSITION DIMENSIONS ARE BASED ON A RECOMMENDED MIN. MTG. HEIGHT OF 8 3/4" [222mm] ABOVE FIN. FLOOR T0 14 3/4"[375mm] WHEN OPEN NOTE 2. FURNISHED WITH (2) WOOD MOUNTING SCREWS Product Description: Drawn: Checked Scale: TMF **JKD** 1:4 SINGLE PEDAL FOOT VALVE WITH Approved Date:

MVW

2/25/00